

HIKOKI

UNLEASH the NEXT

Cordless
Random Orbit Sander

18V SV 1813DA

BRUSHLESS

NEW



Approx.
14%^{*2}
More
Performance

Approx.
80%
Dust
Extraction

Cordless. Powerful. Low Dust.

Greater Performance than Coded, High Dust Extraction Rate

*Vs. the SV 13YB coded random orbit sander. The value is shown for reference purposes and may vary according to the state of battery charge and other operating conditions.

Cordless. Powerful. Low Dust.

Greater Performance than Coded,
High Dust Extraction Rate

Approx. **45 min***1 Runtime per Charge
Using BSL1850C Battery
Workpiece: Pine Wood / Pressing Load: 19.6N (2kgf) / Sanding Paper: A-P80



Sanding Performance¹

Workpiece: Pine Wood / Pressing Load: 19.6N (2kgf) / Sanding Time: 5 minutes / Sanding Paper: A-P80


Cordless
SV 1813DA
Conventional Model
Corded SV 13YB



Approx. **14%**^{*2}
More

Dust-Seal Switch

Helps protect against dust for longer switch life



Dust Extraction Adapters

Available for multiple dust extractors



Variable Speed Dial

Allows for setting the ideal sanding speed for your application



Speed Settings for Different Applications

The chart below is just for reference. Adjust the speed accordingly to achieve the desired results.

Material		Grit Size		Dial
		Rough	Fine	
Paint	Sanding	180	400	3 - 6
	Repairing Scratches and Rust Spots	120	240	2 - 4
	Stripping	40	80	2 - 4
Wood	Soft Wood	60 - 80	240	3 - 6
	Hard Wood	60	180	3 - 5
	Veneer	240	320	2 - 4
Metal	Aluminium	80	240	2 - 4
	Steel	60	240	3 - 6
	Stainless Steel	120	240	3 - 6

Cordless Random Orbit Sander

18V SV 1813DA

NEW



BRUSHLESS

Specifications

Model	SV 1813DA	
Voltage	18V	
Capacity	Sanding Pad	125mm
	Sanding Paper	125mm
Orbit Dia.	3mm	
No Load Speed	7,000 - 11,000/min	
Overall Height	153mm (without Battery)	
Weight*3	1.8kg (with BSL1850C)	
	2.2kg (with BSL36B18)*4	
Standard Accessories*5	2 Batteries (BSL1850C), Charger (UC18YFSL), Sanding Paper, Vacuum Adaptor (A) / (B), Dust Bag	

*1. The value shown is for reference purposes and may vary according to the battery status and other operating conditions.

*2. Vs. the SV 13YB corded random orbit sander. The value is shown for reference purposes and may vary according to the state of battery charge and other operating conditions.

*3. Weight: according to EPTA-Procedure 01/2014.

*4. Sold separately.

*5. Standard accessories vary by country or area.

Distributed by: